

AquaView 50-serie SV-AQV 53 / 54

Mini Sub Sea IP Camera with / without dimmable LED lights, for depth down to 200m



AquaView 53 is a miniature IP Subsea camera with dimmable LED light.

AquaView 54 is a miniature IP Subsea camera without LED light.

The quality and performance are very high despite the compact size.

The customer can choose between different cable types and length together

with fixed subsea connector **SV-AQV53C** or **SV-AQV54C**,

or PG cable gland **SV-AQV53PG** or **SV-AQV54PG**

AquaView 50-serie SV-AQV 53 / 54

Mini Sub Sea IP Camera with / without dimmable LED lights, for depth down to 200m

AquaView 53 / 54 - IP	
Material:	POM – black (Poly Oxy Methylene)
Length:	97mm (without connectors)
Diameter:	Ø = 47mm
Weight:	175g (with connector)
Cable Gland / Connector:	PG-type or Subsea connector
Max External Water Pressure:	25 bar
Max Internal Pressure:	2 bar
Working Temperature:	-20 + 50 grader C
Sensor	1/2.9" 1080P
Lens	2.1 mm 3MP
Resolution	1920 x 1080
Power	12VDC
Consumption:	1 W / With light 3.7 W
Minimum illumination:	Color 0.01 lux @ F1,2 B/W 0.001 lux @ F1.2
WDR:	>80db
Auto White Balance:	Auto
IR-Cut Filter	Yes
Video compression	H.265 / H.264
Shutter	Auto, 1/25 ≈ 1/10000s
Protocol	TCP/IP,UDP,RTP,RTSP,RTCP,HTTP,DNS, DDNS,DHCP,FTP,NTP,PPPOE,SMTP,UPNP
Onvif	Onvif v2.6
Bit Rate	128Kbps-3072bps



PG Cable gland

SEAVISION™

www.seavision.no

info@seavision.no

+47 33 30 42 23